

Press Specifications

Press:	Clearing	Clearing	Verson	Clearing	Cincinnati	Cleveland	Wean-McKay	Minster	Toledo	Toledo
Tonnage	1500	1000	1000	600	600	450	250	250	200	200
Type of Press	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
Rolling Bolster	Yes	Yes	Yes	Yes	-	Yes	-	-	-	-
Bolster Size Front to Back	72	84	72	72	48	80	48	46	45	37
Bolster Size Left to Right	144	144	132	144	168	132	84	90	60	59
Air Cushion	NA	NA	7.00	NA	6.00	NA	NA	6.50	NA	6.00
Max. Shut Ht. (w/o risers)	59.38	59.88	44.30	50.63	38.50	61.30	32.50	38.38	23.50	26.50
Min. Shut Ht. (w/o risers)	42.13	45.88	28.30	26.63	32.50	51.30	24.75	26.25	18.50	21.00
Max. Shut Ht. with risers	43.38	39.88	32.80	NA	23.75	35.30	26.50	26.50	15.63	21.00
Min. Shut Ht. with risers	26.13	25.88	16.80	NA	17.75	25.30	18.75	14.38	10.63	15.75
Ram Adjustment	17.25	14.00	16.00	24.00	6.00	10.00	7.75	12.13	5.00	5.25
Stroke Length	18.00	28.00	14.00	24.00	8.00	24.00	16.00	14.00	10.00	10.00
Strokes per Minute	12	15	12	16	47	20	20	28	24	50
Width of Window	68.00	72.00	54.00	48.00	48.00	46.00	21.25	16.00	8.50	8.50
Coil Feeder	No	Yes	No	No	No	No	No	No	No	No
Max. Coil Width	-	48.00	-	-	-	-	-	-	-	-
Max. Coil Weight	-	6,000	-	-	-	-	-	-	-	-
Coil I.D. Range	-	18" – 22"	-	-	-	-	-	-	-	-
Max. Coil O.D.	-	72.00	-	-	-	-	-	-	-	-
Max. Stock Thickness	-	0.200	-	-	-	-	-	-	-	-